



A REVOLUTION IN VISITOR SIGNAGE

TOTEM-WiFi INFOBOT



The TOTEM-WiFi system is a unique and patented product. Anyone with a smart phone, tablet or laptop with Wi-Fi capability and a modern web browser can connect to TOTEM-WiFi and view your customised information. It is free to use, nothing to pay, nothing to download.

TOTEM-WiFi simplified:



LWiFi
Localised Wifi
Infobot
with lighting






No app
required!
**Optional 4G
Optus Wi-Fi**

Integrated
design allows
for easy
installation

6m fixed or tilt
TOTEM pole

Modular
surface mount
Foundation
System

TOTEM-WiFi Explained

How to setup TOTEM-WiFi	About
 Login	<p>What is TOTEM-WiFi? TOTEM-WiFi gets people connected to your message on any mobile device, even when outside of a network coverage area. It provides a dedicated, standalone, self-powered, free to use local network allowing users to access your audio, video, PDFs or written content instantly.</p>
 Manage media content	
 Publish media on the USB device	<p>Where is TOTEM-WiFi used? TOTEM-WiFi is perfect for installation in any location outside a mobile network. No area is too remote: lookouts, trails and camp grounds are just some of the many places TOTEM-WiFi can be used to provide your information when and where it is needed.</p>
 Plug into your totem	
 Public users	<p>Who uses TOTEM-WiFi? TOTEM-WiFi is ideal for industries such as tourism, government, airports and local councils. The most common use is meeting the needs of tourism and public safety in remote areas.</p>
	<p>If Optus is available the user can connect to free 4G Wi-Fi for a predetermined time.</p>

For more information please contact

Phone: 0417 837 621 E-mail: enquiries@totemwi-fi.com.au

Web: www.totemwi-fi.com.au

TOTEM-WiFi Specifications



Solar TOTEM-WiFi **LWiFi** Unit

Solar part number: TWSLWIFI-4G

Totem WiFi unit	Proprietary patent
Solar panel:	18V/80W High efficiency Monocrystal panel 12V/10 to 30W High Lumens, chip from USA Over 36 hours, considering 3-5 rainy days
Power consumption	12 Watts @ 12 volts Totem/Lighting 15 to 30 watts at 32 Volts (combined 40 Watts at 12v)
LED Lamp:	3000-6500K(optional)
Colour Temperature: Lumen(LM): Discharge time: inc Totem	1800~3400
Working temperature:	-20~+60 degrees
Waterproof rate:	IP65 Operational mounting height 6m
Fitting Wind loading	55m/s
Product size:	1078*451*43mm
Product weight:	18.7KG
Optus 4G ready	SIM configured during manufacturing process

240V TOTEM-WiFi **LWiFi** Unit

240V part number: TW240LWIFI-4G

Totem WiFi unit	Proprietary patent
240v AC Power	12/110/240 Volt AC Totem WiFi Unit (Pre order voltage)
Power consumption	(Power pack) 3 Amps at 240V or Direct connect 1 Amp @ 12 volts
Working temperature:	-20~+60 degrees
Waterproof rate:	IP65 Operational
Fitting Wind loading	55m/s
Product size:	200W x 300H x 150D mm
Product weight:	3.1 KG
Optus 4G ready	SIM configured during manufacturing process



6m Fixed or Tilt Pole

Fixed Pole part number: TW6MFX

Tilt Pole part number: TW6MTILT

Stilmark Fixed Pole	6m Fix Steel Galvanised Pole Refer to Stilmark Specification sheet
Stilmark Tilt Pole	6m Tilt Steel Galvanised Pole Refer to Stilmark Specification sheet



Modular IFS Foundation System

4 x IFS block pack part number: TWIFS4

4 x IFS Foundation Modular block System	Surface Mount Interlocking system complete with locking cleats : refer to IFS Foundations Sheet Web : www.ifsconstruction.com.au
---	--

